TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 cor. Secs. 5 & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 16 Page(s) 6664

A fir, 40" dia., from which
An ash, 12" dia., bears N.70°W., 24 lks.
A cedar, 36" dia., bears S.10°W., 12 lks.

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 16 Page 6691A)

Set a basalt stone, 12x10x6" 8" in the ground, ¼ sec. cor. marked ¼ on N face, from which
A R.Fir, 7" dia., bears N.18°E., 47 lks., mkd: ¼ S5 BT.
A R.Fir, 40" dia., bears S.80°W., 10 lks., mkd: ¼ S8 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - June 1968 - C.S. File 54/59-92

Found - Possible corner stone, no legible marks.
40" now 42" D.Fir S.8°W., 6.6 ft. opened for scribe "B"
7" now 10" D.Fir N.13°E., 32.0 ft. opened, no scribing, old face.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1968 ¼ T30S R1W S 5 / S 8

New BTs- 11" D.Fir S.88°E., 9.4 ft. mkd: ¼ S8 CS BT.
12" Yew N.80°E., 27.3 ft. mkd: ¼ S5 CS BT.