

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 5; & S 32, T29-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

1970 BT, a 9" W.Fir S.64°W., 14.9 ft. with healed double blaze.
No new monument or accessories. I cemented rock tablet to iron post.

Russell Badgley - 7/2021 - C.S. File 65/109-24

Found - A 2" iron pipe, firmly set, projecting 6" above the ground, and original stone alongside, with a 2½" dia. brass cap (properly) marked
Original BTs by Mensch in 1904: Down, out of position, and rotting
BTs by Hoffbuhr in 1970:
A 23" dia. D.Fir bears (N.70¼°E.) (35.3 ft) with a healed blaze.
SW BT not found
BT by "LP6" in 2004 (no record):
A 15" dia. D.Fir bears (S.53°29'E.) (59.54 ft) with a healed double blaze.
New BTs- A 8" dia. G.Fir bears N.81°15'W., 39.2 ft scribed "¼ S32" & "BT" on a double blaze, with a 1" brass washer stamped "BADGLEY PLS70716" nailed into the lower blaze.
A 19" dia. D.Fir bears N.37°30'E. 26.1 ft scribed "¼ S32" & "BT" on a double blaze, with a 1" brass washer stamped "BADGLEY PLS70716" nailed into the lower blaze
Note - The corner falls at the corner of a fence running West and South from this location.
All BTs have BT Tags attached. All new BTs have double blazed faces with bearing measured to the center of the tress at the root crown and distances measured to a nail in the side and center of the root crown.
COMPASS DECLINATION: 14°30'E.