

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 279600

PRIMARY CORNER DESCRIPTION CC Secs. 4 & 5 (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 16 Page 6690)

Set a basalt stone 15x8x6", 10" in the ground for cor. of secs. 4 & 5 mkd with 4 notches on E edge, from which
A fir, 18" dia. bears N.78°E., 64 lks. mkd: T30S R1W S4 BT
A yew, 14" dia. bears N.13°W., 50 lks. mkd: T30S R1W S5 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - June 1968 - C.S. File 54/59-95

Found - 15x8x6 stone firmly set, 4 grooves on the east side. 18" now 23" D.Fir N.78°E., 42.2 ft shows good scars. 14" now 15" yew N.13°W., 33.0 ft., scribe visible, "S5 BT".

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T30S R1W
OFFICE S 5 | S 4
S 8

Bearing Trees ok & tagged.
Note - This corner lies 49.3 ft. west of 8|9