

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 28, 29, 32, & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 73 dated June 8, 1857 - (DCSO Records Vol 16 Pg 6660

Set post corner secs. 28, 29, 32, & 33, from which
A Sugar pine, 48" dia., bears S.48°E. 36 lks.
A fir, 10" dia., bears S.35°W. 7 lks.
A fir, 18" dia., bears N.45°E. 14 lks.
A fir, 18" dia., bears N.55°W. 39 lks.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Jan. 1968 - C.S. File 54/59-19

Found - Orig. 18" fir now 22" snag, N.55°W., 25.7 ft. opened for scribe.

Orig. 48" Pine, now stob, S.48°E., 23.8 ft. shows scar.

Stump hole S.35°W., 4.6 ft. - No trace of NE BT.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T30S R1W
OFFICE S 29 | S 28
1967 S 32 | S 33

New BTs- 17" D.Fir N.25°W., 43.8 ft. mkd: T30S R1W S29 CS BT
20" Cedar N.56°E., 28.2 ft. mkd: T30S R1W S28 CS BT
14" Cedar S.28½°E. 73.6 ft. mkd: T30S R1W S33 CS BT
21" Cedar S.8°W., 47.2 ft. mkd: T30S R1W S32 CS BT

Fd OK by DCSO, SJF & JL 2/2019 - C.S. File 67/46-1

Lat: 42°55'52.82756227" Long: 122°50'34.392857200"