

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor Secs 20, 21, 28, & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 73 dated June 8, 1857 - (DCSO Rec. Vol. 16 Pg 6661

Set post corner secs. 20, 21, 28 & 29, from which
A fir, 12" dia., bears N.60°W. 33 lks.
A fir, 9" dia., bears S.85°W. 28 lks.
A laurel, 12" dia., bears N.70°E. 60 lks.
A cedar, 9" dia., bears S.2°E. 77 lks.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Jan. 1968 - C.S. File 54/59-21

Found - Orig. 12" D.Fir, now 30" dead, N.60°W., 21.8 ft. opened for scribe.
Orig. 9" now 12" Cedar, dead, S.2°E., 50.8 ft., burnt out.
No trace of NE nor SW BTs.
Set - Brass cap at sec. cor. mkd: COUNTY SURVEYORS T30S R1W OFFICE S 20|S 21 1967 S 29|S 28
New BTs- 18" Cedar S.3½°E., 72.2 ft. mkd: T30S R1W S28 CS BT.
20" Cedar S.53°W., 39.5 ft. mkd: T30S R1W S29 CS BT.
34" D.Fir N.81°W., 68.0 ft. mkd: T30S R1W S20 CS BT.
10" Laurel N.79°E. 25.6 ft. mkd: T30S R1W S21 CS BT.

Bruce Shaner, PLS 430 - For: USFS - Jan. 1981 - RM 3-43

Found - 1967 County Brass cap properly marked.
30" D.Fir snag, orig BT scribes visible bears N.62°W., 23.0 ft. (Co. rec. N.60°W., 21.8 ft.)
12" Cedar windfall, orig. BT burnt out face, bears S.2°E., 50.8 ft.
26" Cedar BT scribes visible bears S.3½°E., 72.2 ft.
24" Cedar BT scribes visible bears S.53°W., 39.5 ft.
34" D stump BT scribes visible bears N.81°W. 68.0 ft
14" Madrone BT scribes visible bears N.79°E. 25.6 ft
New BT- 10" Cedar BT, I scribed "T30S R1W S20 BT" bears N.35°W., 37.7 ft.

David Edwards - For: Ireland & Sierra Pacific Industries - 3/2023 - M181-80

Found - DCSO brass cap.
23" Madrone bears N.80°E., 26.3'
27" Cedar bears S.53°21'W., 39,6'
23" Cedar bears N.35°W., 37.7'
All with healed blaze
New - A 5.5' steel post is set 2' south.

