

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, 17, 20, & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 73 dated June 8, 1857 - (DCSO Records Vol 16 Pg 6662

Set post & build stone mound corner secs. 16, 17, 20 & 21, from which
 A pine, 12" dia., bears S.45°W. 31 lks.
 A pine, 12" dia., bears N.75°E. 122 lks.
 An Oak, 6" dia., bears S.30°E. 26 lks.
 An Oak, 12" dia., bears N.30°W. 94 lks.

Douglas Co. Surveyors Office - John M. Powell - 1/1968 - C.S. File 54/59-33

Reported as not found.
Fd pine S.45°W., which had been opened old forestry tag 1941.
No BTs or no trace of mound of stone.

Larry J. Friar - For: USFS - Feb. 1976 - M56-37

Set - 2" pipe with 3" brass disk top properly stamped, from which
 A 20" fir bears N.69°45'W., 44.6 ft. scribed T30S R1W S17 BT.
 A 36" Twin cedar, bears N.72°30'E., 33.9 ft. scribed T30S R1W S16 BT.
 A 36" cedar bears S.22°30'E., 29.6 ft. scribed T30S R1W S21 BT.
 A 20" Fir bears S.65°30'W., 67.3 ft. scribed T30S R1W S20 BT.

1