

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 16 Page 6691B)

-----  
Set a slate stone 12x8x6", 8" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which

- A R.Fir, 10" dia., bears N.2°E., 61 lks., mkd: ¼ S9 BT.
- A Maple, 10" dia., bears S.52°W., 37 lks., mkd: ¼ S8 BT.

-----  
Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - June 1968 - C.S. File 54/59-97

-----  
Found - No trace of the corner stone nor NE BT.  
10" now 14" Maple S.52°W., 24.4 ft., fd reverse scribing.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T30S R1W OFFICE 1968 ¼ S 8|S 9

New BTs- 9" Hemlock, N.74°W., 34.6 ft. mkd: ¼ S8 CS BT.  
22" Yew, N.52°E., 51.6 ft. mkd: ¼ S9 CS BT.

Note - This ¼ corner lies on N slope, approx. 100' S of a small swamp.

-----  
David Bateman - For: USFS - June 16, 1978 - M72-25

-----  
Found - 1968 Doug. Co. brass cap  
22" Yew Stump, N.52°E., 51.6 ft.  
10" Hemlock (down) N.74°W., 34.6 ft scribing visible  
12" Maple S.52°W., 24.4 ft. rotten (orig.)

New BTs- 12" Yew, N.57°E., 104.0 ft. "¼ S9 BT"  
30" I.Cedar, N.8°W., 148.3 ft. "¼ S8 BT"