

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION CC Secs. 8 & 9 (North)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 16 Page 6690)

Set an ironstone 20x12x8", 15" in the ground for closing corner of secs. 8 & 9, marked CC on S with 4 grooves on E & 5 grooves on S faces; from which

A W.Fir, 10" dia., bears S.11°E., 37 lks., mkd: T30S R1W S9 BT.

A W.Fir, 10" dia. bears S.2°W. 82 lks. mkd: T30S R1W S8 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - June 1968 - C.S. File 54/59-94

Found - Stone 20x12x8, firmly set, "CC on S & 4V on E.
10" W.Fir, now rotten stump S.11°E., 24.1 ft.
No trace of SW BT

Set - Brass cap at Cor. mkd: COUNTY SURVEYORS T30S R1W
OFFICE S 4
1968 S 8 | S 9

New BTs- 26" double yew S.64°W., 41.6 ft. mkd: T30S R1W S8 CC CS BT.

7" Yew S.42°E., 8.1 ft. mkd: T30S R1W S9 CC CS BT.

Note - This corner lies 49.3 ft. East of corner 5|4.