

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 16 Page 6691)

Set a basalt stone 14x8x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which

A fir, 30" dia., bears S.18°E., 23 lks., mkd: ¼ S4 BT.

A fir, 48" dia., bears N.88°W., 12 lks., mkd: ¼ S5 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - June 1968 - C.S. File 54/59-96

Found - No trace of stone at corner.

48" D.Fir down & rotten N.88°W., 7.9 ft., opened, found reverse scribing.

30" D.Fir now snag, S.18°E., 15.2 ft. no scribing found.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T30S R1W
OFFICE 1968 ¼ S 5 | S 4

New BTs- 9" Hemlock N.9°W., 19.7 ft. mkd: ¼ S5 CS BT.

16" D.Fir N.33°E., 37.7 ft. mkd: ¼ S4 CS BT.