

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 33 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6648)

Set ¼ sec. post, from which
A Yew 18" dia., bears N.10°E., 18 lks.
A Fir 12" dia., bears S.10°W., 20 lks.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6707)

The old ¼ sec. cor. located by reference to the original bearing trees. From cor. point
A Yew 20" dia., bears N.10°E., 18 lks. dist. mkd. ¼ S BT.
(Old BT)
A Fir 18" dia., bears S.10°W., 20 lks. dist. mkd. ¼ S BT.
(Old BT)

I now change this cor. to refer to sec. 33 only, and obliterate the marks on the bearing tree SW. of cor.

At exact cor. point
Set an iron post 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor. of sec. 33 only, with brass cap: ¼ S 33
1923

from which
A Cedar 12" dia., bears N.60°W., 19 lks. dist. mkd. ¼ S33 BT. (New BT)