TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 73 dated June 8, 1857 - (DCSO Records Vol 16 Pg 6665

Set ¼ sec. post, from which
A Fir, 24" dia., bears N.10°W. 20 lks.
A fir, 6" dia., bears S.85°W. 68 lks.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Jan. 1968 - C.S. File 54/59-25

Found - Orig. 6" now 13" D.Fir S.85°W., 44.9 ft. tree previously opened, reopened for ring count, scribe visible "¼S" ring count, rings very close, approx. right age.
No trace of NW BT.
Set - Brass cap at ¼ cor. mkd: COUNTY SURVEYORS OFFICE 1968 T30S R1W ¼ S 28 / S 33
New BTs- 17" D.Fir N.10°W., 36.3 ft. mkd: ¼ S28 CS BT.
13" D.Fir S.36°W., 15.2 ft. mkd: ¼ S33 CS BT.

David Edwards - For: Ireland & Sierra Pacific Industries - 3/2023 - M181-80

Found - DCSO brass cap.
14" dia., Fir bears S.36°W., 15.2'
24" dia., Fir bears N.10°W., 36.3'
Both with healed blaze.
New - A 5.5' steel post is set 2' North.