

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 340400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 73 dated June 8, 1857 - (DCSO Records Vol 16 Pg 6667 ----- Set ¼ sec. post, from which An Oak, 12" dia., bears N.30°E. 34 lks. An Oak, 18" dia., bears S.75°W. 42 lks.</p>
<p>Douglas Co. Surveyors Office - John M. Powell - 1/1968 - C.S. File 54/59-43 ----- Reported as not found. Approx. cor. is close to very old fence cor. old oak stump burnt probably SW tree. Location tag a approx. cor.</p>
<p>Larry J. Friar - For: USFS - Feb. 1976 - M56-37 ----- Set - 2" pipe with 3" brass disk top properly stamped, from which A 18" Fir, bears S.35°30'E., 61.6 ft. scribed ¼ S21 BT. A 16" Fir, bears S.39°W., 51.5 ft. scribed ¼ S21 Bt.</p>
<p> </p>