TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

---

GLO survey by Dennis Hathorn, US Deputy Surveyor, contract 73 dated June 8, 1857 - (DCSO Records Vol. 16 Page(s) 6668

---

Set ¼ sec. post, from which
An Oak, 36" dia., bears S.22°W., 80 lks.
An Oak, 24" dia., bears N.62°W., 14 lks.

---

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 16 Page 6694)

---

This corner is partly obliterated. The post is greatly decayed & marks on BTs are deeply overgrown. I destroyed the old marks & reestablished the corner in its orig. position as follows:
Set a basalt stone 14x10x8", 9½" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A W.Oak, 30" dia., bears N.62°W., 14 lks., mkd: ¼ S9 BT.
A B.Oak, 40" dia., bears S.22°W., 80 lks., mkd: ¼ S16 BT.

---

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - June 1968 - C.S. File 54/59-93

---

Found - 40" B.Oak, rotted out, S.22°W., 52.8 ft.
30" W.Oak, now 29" N.62°W., 9.2 ft., shows good scar
14x10x8 stone, "¼" on N face.
Set - Brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1968 ¼ T30S R1W S 9 / S 16
New BT - 8" D.Fir S.38°W., 30.0 ft. mkd. ¼ S16 CS BT.
Reblazed & rescribed 29" W.Oak N.62°W., 9.2 ft. mkd. ¼ S9 CS BT.
Note - Corner lies 1.0 ft. W. of old N-S fence line.

---