

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 73 dated June 8, 1857 - (DCSO Records Vol. 16 Page(s) 6665

 Set post corner secs. 27, 28, 33, & 34, from which
 A fir, 10" dia., bears S.82°E., 45 lks.
 A fir, 18" dia., bears N.32°W., 23 lks.
 A laurel, 10" dia., bears S.11°W., 9 lks.
 A dogwood, 3" dia., bears N.46°E., 22 lks.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Dec. 20, 1967 - C.S. File 54/59-5

 Found - Mound of stone at section corner.
 18" now 31" D.Fir N.32°W., 15.2 ft. faint bark scribes visible.
 10" now 13" D.Fir S.87°E., (Rec. S.82°E.) 29.7 ft. opened for scribe "S 3"
 No trace of other BTs

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T30S R1W
 OFFICE 1967 S 28 | S 27
 S 33 | S 34

New BTs- 10" D.Fir N.74°E., 19.4 ft. mkd: T30S R1W S27 CS BT
 12" Cedar S.72°E., 31.5 ft. mkd: T30S R1W S34 CS BT
 11" D.Fir S.19°W., 28.4 ft. mkd: T30S R1W S33 CS BT
 31" D.Fir N.72°W., 18.0 ft. mkd: T30S R1W S28 CS BT

Maurice E. Farr, LS 1181 - For: USFS - Leonard Herzstein - Randy Lopez - Sept. 18, 1984 - C.S. File 62/15-6

 Found - 1½" O.D. iron pipe with brass cap attached, firmly set, projecting 12" above a 3 ft. dia. mound of stone. IP is leaning slightly northerly & brass cap is rotated 45° clockwise. I use point where the IP projects from the mound of stone as the corner point. 1967

Orig. BT a 13" D.Fir S.87°E., (Rec. S.82°E.) 29.7 ft. with scribe marks "S3" visible on previously opened blaze.

Orig. BT A 32" D.Fir stump, N.32°W., 15.2 ft. with no marks visible.

BTs marked in 1967:

Found - 12" D.Fir, N.74°E., 19.4 ft with healed double blaze
 14" I.Cedar, S.72°E., 31.3 ft. (Rec. 31.5 ft.) with partially healed double blaze.

10" D.Fir snag, S.19°W., 28.4 ft. with scribe marks "T30S R1W S33 CS BT"

continued next page

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Cor. Secs. 27, 28, 33, & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 36" D.Fir N.72°W., 17.4 ft. (Rec. 18.0 ft.) with healed blaze.
New BT - A 13" madrone, S.55°W., 26.6 ft. scribed "T30S R1W S33" on upper bark blaze & "BT" on foot blaze with a brass washer stamped "LS 1181" nailed to face of lower blaze.
Note - Steel fence post set 3.7 ft. south with USFS signs #54-2 & #54-4 attached. Corner is 40 ft. NW of new USFS road now under construction & 300 ft. ± from its junction with USFS Rd. #31

Fd. Ok 6/1991 - C.S. File 63/78
FD. Ok by B. Shaner 9/1992 - RM 3-76