

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27 & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 73 dated June 8, 1857 - (DCSO Records Vol 16 Pg 6666

Set post corner secs. 21, 22, 27 & 28, from which
A fir, 36" dia., bears N.70°W. 15 lks.
A fir, 9" dia., bears S.10°E. 32 lks.
A chinquapin, 6" dia., bears S.74°W. 46 lks.
A fir, 30" dia., bears N.80°E. 51 lks.

William Ruppert, PLS 866 - For: USFS - Jan. 1978 - M65-66 & C.S. 58/156

Set by proportionate methods.
Set - 2"x30" Gal. I.P. with brass cap stamped T30S R1W S21
S22 S28 S27 RLS 866 1978.
BTs - 12" D.Fir, N.30°08'E., 23.6 ft. "T30S R1W S22 BT".
14" D.Fir, S.85°16'E., 19.6 ft. "T30S R1W S27 BT".
18" D.Fir S.15°20'W., 38.7 ft. "T30S R1W S28 BT"
19" D.Fir N.51°28'W., 33.8 ft. "T30S R1W S21 BT".