TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor. Secs. 15, 16, 21, & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

---

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 73 dated June 8, 1857 - (DCSO Records Vol 16 Pg 6667

---

Set post corner secs. 15, 16, 21, & 22, from which
An Oak, 10" dia., bears S.47°W. 38 lks.
An Oak, 9" dia., bears N.32°E. 32 lks.
An Oak, 18" dia., bears N.50°W. 100 lks.
A Pine, 36" dia., bears S.60°E. 56 lks.

---

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Jan. 1968 - C.S. File 54/59-42

---

Found - 18" now 23" W.Oak N.50°W., 66.0 ft. opened for scribe "B"
Pine stump hole S.66°E., 37.0 ft.
No trace of NE nor SW BTs.

Set - Brass cap at sec. cor. mkd: COUNTY SURVEYORS T30S R1W

| OFFICE | S16 \| S15 |
|---|---|
| 1968 | S21 \| S22 |

New BTs- 12" D.Fir N.54°W., 3.0 ft. mkd: T30S R1W S16 CS BT.
11" D.Fir N.56½°E., 10.0 ft mkd: T30S R1W S15 CS BT.
14" D.Fir S.53°E., 23.4 ft. mkd: T30S R1W S22 CS BT.
12" D.Fir S.53°W., 22.0 ft. mkd: T30S R1W S21 CS BT.

---

Loyd R. Moffit - For: USFS - Dec. 1985 - C.S. 62/30-42

---

Found - A 2½" brass cap on 1" iron pipe exposed 8". Corner remonumented in 1968 by the county.

New BT - Marked a 9" Fir BT which bears N.73°E., 8.5 ft. scribed T30S R1W S15 BT.

---