

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 73 dated June 8, 1857 - (DCSO Records Vol 16 Pg 6668  
-----  
Set ¼ sec. post, from which  
    An Oak, 15" dia., bears S.75°E. 25 lks.  
    An Oak, 10" dia., bears N.56°W. 118 lks.

Douglas Co. Surveyors Office - Frank Cain, Deputy - Recorded by F.C. Frear, Co. Surveyor - Nov. 24, 1920 - FB 107 Pg 70  
-----  
Renewed by setting an rock from which  
    A pine 10" dia., bears N.73°35'E., 143 lks.  
    A pine 8" dia., bears S.57°05'W., 144 lks.

Douglas Co. Surveyors Office - Dennis Gaylord, Deputy & USFS - Roland Simshauser - Nov. 10, 1977 - C.S. File 59/42-9  
-----  
Found - 26x16x10" stone set solidly in place. No marks visible. Stone is 5" out of ground.  
    A 31" Pine stump, orig. 10", bears N.75½°E., 94.8 ft. (Rec. 94.38 ft) scribing visible "S ¼ S" 1920  
    A 15" Ponderosa Pine orig. 8", bears S.57°W., 94.1 ft. scribing visible on previously opened blaze, "S ¼ (Rec. dist. is 95.04'  
Set - Moving the stone aside, I SET in its place a 2½" brass cap on 1½" Galv. I.P. I buried the corner stone alongside. Brass Cap stamped: County Surveyor's Office T30S R1W ¼ S16 S15 1977  
New BTs- A 10" D.Fir bears S.39°E., 50.7 ft. scribed "¼ S15 CS BT" on a double blaze.  
    A 11" Oak bears S.55°W., 67.3 ft. scribed "¼ S16 CS BT" on a double blaze. I placed county BT signs on all 3 living BTs.