

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 73 dated June 8, 1857 - (DCSO Record Vol 16 Pg 6669)</p> <p>-----</p> <p>Set ¼ sec. post, from which A fir, 18" dia., bears N.40°E. 22 lks. A fir, 18" dia., bears N.30°W. 42 lks.</p>
<p>GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 16 Page 6691C)</p> <p>-----</p> <p>The ¼ sec. cor. is not found after careful search.</p> <p>....</p> <p>Set a basalt stone 12x8x6", 8" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which A R.Fir, 20" dia., bears S.76°E., 22 lks., mkd: ¼ S10 BT. A R.Fir, 40" dia., bears West, 20 lks., mkd: ¼ S9 BT</p>
<p>Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Feb. 1968 - C.S. File 54/59-78</p> <p>-----</p> <p>Found - Corner stone 12x8x6 with "¼" on west side. 20" now 28" R.Fir S.76°E., 14.5 ft. with good face. 40" R.Fir now 42" snag, west 13.2 ft shows good brk scribing.</p> <p>Set - Brass cap at cor. mkd: COUNTY SURVEYORS T30S R1W OFFICE 1968 ¼ S 9 S10</p> <p>New BT- 30" R.Fir N.42½°W., 14.1 ft. mkd: ¼ S9 CS BT.</p> <p>Note - This corner lies on flat ground.</p>
<p>David K. Bateman - For: USFS - June 16, 1978 - M72-25</p> <p>-----</p> <p>Found - 1968 Doug. Co. Brass cap 30" D.Fir N.43°W., 14.1 ft. scribing visible. 42" D.Fir snag, West 13.2 ft. (Orig.) 28" D.Fir stump, S.76°E., 14.9 ft healed face (Orig)</p> <p>New BTs- 12" D.Fir bears N.32°W., 44.7 ft. scribed "¼ S9 BT"</p>
<p>Loyd R. Moffit - For: USFS - Dec. 1985 - C.S. 62/30-40</p> <p>-----</p> <p>Found - 2½" brass cap on 1" iron pipe exposed 16". Corner re-monumented in 1968 by County.</p> <p>New BT - Marked a new 8" Oak BT which bears S.56°E., 97.7 ft. from the corner scribed ¼ S10 BT.</p>
<p>Fd. Ok by B. Shaner, 7/1999 - M132-9 & C.S. File 65/23-15</p>