

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 16 Page 6689)

-----  
A R.Fir 30" dia., for 1/4 sec. corner, I mark 1/4 S4 on W side & 3 on E side; from which  
    A hemlock, 14" dia., bears S.12°E., 40 lks., mkd: 1/4 S3 BT.  
    A W.Fir, 12" dia., bears N.87°W., 22 lks., mkd: 1/4 S4 BT.

-----  
Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - June 1968 - C.S. File 54/59-99

-----  
Found - 30" now 38" fir corner tree, opened for scribe "3"  
        12" W.Fir now stob, N.87°W., 14.5 ft., opened for scribe "1/4"  
        14" hemlock, now rotten stump, S.12°E., 26.4 ft.  
Set - Brass cap on S. Side of corner tree mkd: T30S R1W  
            COUNTY SURVEYORS OFFICE 1968 1/4 S 4 | S 3  
New BTs- 6" yew S.32°E., 13.0 ft. mkd: 1/4 S3 CS BT.  
        26" D.Fir N.30°W., 18.0 ft. mkd: 1/4 S4 CS BT.