

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 400700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3 & 4; & 33 & 34, T29-1

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Contract #757, dated Sept. 14, 1904 - (DCSO records Vol. 14 Page(s) 6068)

-----  
A Cedar 10" dia. for cor. of secs. 3, 4, 33 and 34, I mark T29S S34 on NE.; R1W S3 on SE.; T30S S4 on SW.; and S33 on NW. side, with 3 notches on E. and W. sides, from which  
A Red Fir 12" dia., bears N.70°E., 59 lks. dist. mkd. T29S R1W S34 BT.  
A Red Fir 15" dia., bears S.10°E., 49 lks. dist. mkd. T30S R1W S3 BT.  
A Cedar 16" dia., bears S.54°W., 19 lks. dist. mkd. T30S R1W S4 BT.  
A Laurel 12" dia., bears N.56°W., 48 lks. dist. mkd. T29S R1W S33 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - June/July 1968 - C.S. File 54/59-100

-----  
Found - 10" now 15" Cedar Corner tree, shows good scars.  
12" now 15" D.Fir N.70°E., 38.9 ft., shows good scar.  
16" now 25" Cedar S.54°W., 12.5 ft., shows good scar.  
12" now 16" Laurel N.56°W., 31.7 ft., shows scar, some scribe marks visible.  
15" D.Fir, now dead, S.10°E., 32.3 ft. opened for scribe "3".

Set brass cap at South side of corner tree marked:  
County Surveyors Office 1968

T 29 S R 1 W  
S 33 | S 34  
S 4 | S 3  
T 30 S

New BT - 6" Laurel S.7°E., 28.0 ft. mkd. T30S R1W S3 CS BT.  
All other BTs OK and tagged.