

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 73 dated June 8, 1857 - (DCSO Records Vol 16 Pg 6670

Set ¼ sec. post, from which
 A pine, 8" dia., bears S.60°W. 12 lks.
 A fir, 8" dia., bears N.88°W. 50 lks.

Reported as not found by JMP, DCSO 1/1968: C.S. File 54/59-53
2 - 8" BTs no trace of same fd. old sq. post but no other
evidence.

William Ruppert - For: USFS - Sept. 1977 - M69-4

Set - Brass cap stamped T30S R1W ¼ S27 S34 RLS 866 1978
 10" D.Fir bears N.64°00'W., 80.7 ft. scribed "¼ S27 BT"
 9" W.Fir bears S.42°42'W., 128.4 ft. scribed "¼ S34 BT"

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy -
S.J. Flause - Sept. 20, 1985 - C.S. 62/29-22

Original post not found
Found - Iron pipe and brass cap set at proportionate
 position (M69-4) firmly set in mound of stone .
 10" fir with partially healed double blaze bears
 N.61½°W. 80.4 ft. (Rec. N.64°W. , 80.7 ft. M69-4)
 from the found monument.
 9" fir now an 11" D.Fir with partially healed double
 blaze bears S.45°W., 127.9 ft. (Rec. S.42°42'W.,
 128.4 ft. M69-4) from the found monument.
 Also found (not noted on M69-4) original 8" diam.
 fir now a partially decayed fir stump approx 18"
 dia. 24" high. Stump has previously opened blaze
 with scribing visible "/4S". We open lower blaze
 and find scribing "BT". We count 110 growth rings
 from blaze to the bark of decayed stump. Record
 bearing and distance to original corner is
 N.88°W., 33.0 ft. See photos in C.S. File 62/29.
Set - At record bearing and distance from the found
 original BT as noted, we SET a 1"x30" galv. iron
 pipe with brass cap attached marked "Douglas
 County Surveyor T30S ¼ S27 S34 R1W 1985".
 Monument is set in stone mound approx 2 ft.
 across base and 2 ft. high.
 The proportioned monument per M69-4 bears N.36½°W.,
 22.9 ft.
New Ties to BTs marked from M 69-4:
 (NW 10" fir) 10" fir with partially healed blaze
 bears N.56°W., 101.6 ft. continued next page

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 34

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

(SW 9" W. fir) 11" D. fir with partially healed
blaze bears S.55½°W., 126.6 ft.
New BTs- 30" D.Fir double blazed and scribed "¼ S27 CS BT"
bears N.14°W., 27.5 ft.
8" madrone bark scribed "¼ S34 CS BT" bears S.1½°W.,
28.1 ft.

Fd. Ok 6/1991 - C.S. File 63/78
FD. Ok by B. Shaner 9/1992 - RM 3-76