

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 27

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 73 dated June 8, 1857 - (DCSO Records Vol. 16 Page(s) 6671

-----  
Set ¼ sec. post, from which  
    An Oak, 10" dia., bears S.18°W. 62 lks.  
    An Oak, 12" dia., bears N.68°E. 33 lks.

John H. Markham, Jr. - For: Stomar Lumber Co. - Oct. 22, 1962  
- C.S. File 51/121-3

-----  
As determined from Old BTs:  
    13" W.O. uproot bears S.18°W., 41.0 ft. OBT.  
    10" W.O. snag bears N.68°E., 21.8 ft. OBT.  
At corner point set 1¼"x36" truck axle with flange up, from which:  
    5" Fir S.33°E., 24.0 ft. mkd: ¼ S27 BT.  
    5" Fir S.34°W., 22.5 ft. mkd: ¼ S XX BT.  
    13" Cedar N.79°W., 51.8 ft. mkd: ¼ S22 BT.  
    8" W.O. N.56°W., 47.0 ft. mkd: ¼ S22 BT.  
Rock road bears S.45°W., 185 ft. dist.

William Ruppert, LS 866 - For: USFS - Jan. 1978 - M65-66 & C.S. 58/156

-----  
Found - 8" Oak snag bears N.68°30'E., 21.8 ft.  
        8" Fir snag bears S.32°55'E. 24.5 ft show good scar.  
        8" Fir snag bears S.34°40'W. 21.5 ft show good scar.  
        15" Cedar N.77°W., 51.0 ft. visible scribe.  
        10" W.Oak N.54°10'W., 47.0 ft. show good scar.  
        1" steel shaft. 6" flange.  
Set - 2"x30" gal. IP with brass cap stamped T30S R1W S22  
      S27 ¼ PLS 866 1977.

Loyd R. Moffit, LS 944 - For: USFS - April 1985 - C.S. 63/8-9

-----  
Found - 2" brass cap on a 2" iron pipe projecting 6" above stone mound. 1978  
        An 8" snag bears S.32°E., 24.5 ft. scar visible.  
        An 8" snag bears S.34°W., 22.5 ft. scar visible.  
        A 16" cedar bears N.64°W., 51.0 ft. scribe visible.  
        A 12" oak bears N.52°W., 47.0 ft. scar visible.  
New BT - A 6" fir which bears S.16°E., 4.3 ft. mkd ¼ S27 BT.