

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 441700

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 34 only, T29-1

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Resurvey by Ernest P. Rands, Deputy Surveyor, Under contract #790, dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6103)

-----  
Set a basalt stone 16x12x10 ins., 11" in the ground for ¼ sec. cor. common to 2 quarters of sec. 34 only, marked ¼ on N. face, from which

A Fir 30" dia., bears N.40½°E., 133 lks. dist. mkd. ¼ S34 BT.

A Pine 30" dia., bears N.51½°W., 120 lks. dist. mkd. ¼ S34 BT. (This Pine is the BT formerly marked as accessory to the old ¼ sec. cor.)

Douglas Co. Surveyors Office - John M. Powell, and crew - Feb. 20, 1968 - C.S. File 54/59-71

-----  
Found - 16"x12"x10" stone marked "¼".  
30" now 34" D.Fir, N.40½°E., 87.8 ft., shows good scar.

30" Pine now 25", N.51½°W., 79.2 ft., shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office  
T 29 S R1W ¼ S 34  
T 30 S 1968

Bearing trees OK and tagged.

Corner lies 33.0 ft. East of ¼ cor. Sec. 3 only, T30-1. Also, 25" Pine, N.51½°W. was used for both corners.