

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35 only (South)

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6648)

Set post corner secs. 34, 35, 2 and 3, from which

- A Fir 18" dia., bears S.40°E., 6 lks.
- A Fir 12" dia., bears N.80°W., 27 lks.
- An Oak 6" dia., bears N.45°E., 54 lks.
- A Pine 24" dia., bears S.20°W., 52 lks.

GLO resurvey by Fred Mensch , U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6710-11)

The old cor. of secs. 2, 3, 34 and 35, located by reference to the original bearing trees. From cor. point,

- An Oak 14" dia., bears N.45°E., 51 lks. dist. mkd. T30S R1W S35 BT. (Old BT)
- A Fir 18" dia., bears S.40°E., 6 lks. dist. mkd. T31S R1W S2 BT. (Old BT)
- A Fir 18" dia., bears N.80°W., 27 lks. dist. mkd. T30S R1W S34 BT. (Old BT)

The old BT referring to sec. 3 is dead and fallen. I now change this cor. to refer to secs. 34 and 35 only, and obliterate the marks on the BT referring to sec. 2.

At exact cor. point

Set an Iron post 3 ft. long, 2" dia., 28" in the ground for cor. of sec. 34 and 35 only, with brass cap marked:

T30S	R1W
S34	S35
T31S	R1W
S2	
1923	

Douglas Co. Surveyors Office - John M. Powell, and crew - July 1968 - C.S. File 54/59-116

Found - GLO brass cap at cor., properly mkd. in 1923.

- 14" now 16" W.Oak N.45°E., 33.7 ft. scribe visible, "35".
- 18" now 36" D.Fir S.40°E., 4.0 ft., shows good scar.
- 18" D.Fir now down, N.80°W., 17.8 ft.

New BT - 12" D.Fir N.2½°W., 15.6 ft. mkd. T30S R1W S34 CS BT. NE. and SE BTs OK and tagged.

Cor. is on W. slope, 207.5 ft. E. of cor. secs. 2 & 3, T31-1

(Cont. Next Page)

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 500100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 34 & 35 only (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Survey by Bruce A. Shaner LS #430 - For: U.S. Forest Service
- April 1980 - RM 3-29

Found - GLO brass cap at cor., properly marked.
14" Oak, orig. BT, snag, scribes visible, bears
N.49°E., 34.5 ft. (Rec. N.45°E., 33.7 ft.)
34" D.Fir, orig. BT, with visible face, bears
S.40°E., 4.0 ft.
14" D.Fir, bears N.2½°W., 15.6 ft. mkd. by DCSO.
New BT - 20" D.Fir bears N.76°E., 35.5 ft. scribed T30S R1W
S35 BT.