

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 33, & 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 73 dated June 8, 1857 - (DCSO Records Vol. 16 Page(s) 6669

Set post corner secs. 26, 27, 34, & 35, from which
A fir, 12" dia., bears N.2°W. 100 lks.
A fir, 10" dia., bears S.75°E. 140 lks.
A Fir, 36" dia., bears S.41°W. 102 lks.
A pine, 20" dia., bears N.70°E. 104 lks.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6719)

The cor. of secs. 26, 27, 34, & 35, located by reference to the orig. BTs, which agree with the field notes except that the BTs in secs. 26 & 34 are dead and fallen.
At exact corner point
Set an iron post, 3 ft. long, 2" dia., 26" in the ground, for cor. of secs. 26, 27, 34, & 35, with brass cap marked
T30S|R1W
S27|S26
S34|S35
1923

from which
A cedar, 12" dia., bears N.27°E., 70 lks., mkd: T30S R1W S26 BT: new BT
A fir, 28" dia., bears S.75°E., 139 lks., mkd: T30S R1W S35 BT: old BT
A pine, 18" dia., bears S.42°W., 83 lks., mkd: T30S R1W S34 BT: New BT
A fir, 24" dia., bears N.2°W., 100 lks., mkd: T30S R1W S27 BT: Old BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Jan. 1968 - C.S. File 54/59-52

Found - GLO brass cap 1923, properly marked in 1923.
12" now 19" cedar N.27°E., 46.2 ft. shows good scar.
20" now 36" D.Fir S.75°E., 91.7 ft. shows good scar.
18" now 26" Pine, S.42°W., 54.8 ft. shows good scar.
24" D.Fir, now snag, N.2°W. 66.0 ft shows good scar.
New BT - 18" S.Pine N.4°W. 42.2 ft scribed T30S R1W S27 CS BT
Other BTS OK & tagged.