

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Sec. 27 only (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 73 dated June 8, 1857 - (DCSO Records Vol. 16 Page(s) 6670

Set ¼ sec. post, from which
A cedar, 24" dia., bears N.10°E., 22 lks.
A pine, 30" dia., bears N.70°W., 55 lks.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6721-2)

The ¼ sec. cor. established for secs. 26 & 27 located by reference to the orig. BTs. I now change this corner to refer to sec. 27 only and
At the exact corner point
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor. of sec. 27 only, with brass cap marked

¼27 |
1923 |

from which
A cedar, 24" dia., bears N.10°E., 22 lks., mkd: ¼ S BT:
old BT
A pine, 30" dia., bears N.70°W., 55 lks., mkd: ¼ S27 BT:
old BT
A cedar, 30" dia., bears S.18°W., 38 lks., mkd: ¼ S27 BT:
new BT.
Obliterate the marks on the old BT NE of corner.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Jan. 1968 - C.S. File 54/59-40

Found - 1923 GLO Brass Cap at ¼ Corner mkd. properly.
30", now 36" Cedar, S.18°W. 25.1 ft. shows good face
24" Pine, now 24" Stub, N.70°W. 36.1 ft., shows scribing.

No trace N.E. BT.
New BTs- 6" D.Fir S.80°W., 16.1 ft. mkd. ¼ S27 CS BT.
6" D.Fir N.31°W. 20.3 ft. mkd. ¼ S27 CS BT.

Note - The ¼ corner of Sec. 26 only, O.K., lies 30.4 ft. North and both corners lie on west slope.