

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 73 dated June 8, 1857 - (DCSO Records Vol. 16 Page(s) 6670-1

-----  
Set post corner secs. 22, 23, 26, & 27, from which  
A fir, 12" dia., bears S.43°W., 42 lks.  
A fir, 12" dia., bears S.38°E., 23 lks.  
A fir, 48" dia., bears N.35°W., 13 lks.  
A fir, 9" dia., bears N.15°E., 44 lks.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6720-1)

-----  
The cor. of secs. 22, 23, 26, & 27 is located by reference to the orig. BTs.

At exact corner point  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 22, 23, 26, & 27, with brass cap marked

T30S R1W  
S22|S23  
S27|S26  
1923

from which  
A fir, 18" dia., bears N.15°E., 44 lks., mkd: T30S R1W S23  
BT. Old BT  
A fir, 20" dia., bears S.38°E., 23 lks., mkd: T30S R1W S26  
BT. Old BT.  
A fir, 20" dia., bears S.43°W., 42 lks., mkd: T30S R1W S27  
BT. Old BT.  
A fir, 48" dia., bears N.35°W., 13 lks., mkd: T30S R1W S22  
BT. Old BT.

Fd Ok DCSO JMP, tagged trees. 12/28/1967 - C.S. File 54/59-16

William Ruppert, PLS #866 - For: US Forest Service - Jan. 1978 - M65-66 & C.S. 58/156

-----  
Found - 1923 GLO brass cap  
29" D.Fir S.34°19'E., 16.2 ft. good scar.  
35" D.Fir S.41°00'W., 27.6 ft. good scar.  
44" D.Fir N.38°34'W., 9.0 ft. good scar  
15" D.Fir N.16°05'E., 29.5 ft. windfall no scribe found.

Scribed- 20" D.Fir bears N.27°07'E. 48.6 ft "T30S R1W S23 BT"