TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 73 dated June 8, 1857 - (DCSO Records Vol. 16 Page(s) 6671

A fir ¼ sec. post, from which
A fir, 12" dia., bears S.35°W., 30 lks.
A fir, 15" dia., bears S.30°E., 26 lks.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6722-23)

The ¼ sec. cor. which is a broken fir stump. The BT in sec. 23 is dead and gone.
Alongside the broken stump
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap marked

¼
S22|S23
1923

from which
A fir, 36" dia., bears S.82°E., 87 lks., mkd: ¼ S23 BT: new BT.
A fir, 18" dia., bears S.35°W., 31 lks., mkd: ¼ S22 BT: old BT.

Reported as not found, DCSO JMP 6/10/1968 - 1923 BC NF. 2 large BTs probably down or burnt, call on ck of about 660.0 good N-S blazed line. After diligent search I could not come up with the corner. C.S. File 54/59-81

Douglas Co. Surveyors Office - Dennis Gaylord, US Forest Service & Deputy Co. Surveyor - Walter Barton, Witness - March 17, 1977 - C.S. File 59/31-10

Found - 1923 GLO brass cap mkd. ¼ S22 S23, Township and range not stamped on brass cap. (T30S R1W). Brass cap 24" above ground and leaning toward center of decomposed stump, all that remains of the orig. corner tree.
A Fir tree bears S.82°E., 57.42 ft. & is blown down. Has healed blaze.
A Fir bears S.35°W., 20.46 ft. and is blown down. Has healed blaze.
Renewal- I remove brass cap & I.P. (which is loose) & place in exact center of the decomposed remains of the orig. corner tree. Top of brass cap is set flush with ground.
continued next page

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

New BTs- A 6" W.Fir bears N.59°30'E., 27.3 ft. scribed "¼ S23 CS BT" on a double blaze.
A 6" W.Fir bears S.34°30'W., 16.6 ft. scribed "¼ S22 CS BT" on a double blaze.

Note - Corner lies on a North slope, South of Jackson Creek in a recently logged area.