

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 500360

PRIMARY CORNER DESCRIPTION N 1/16 Cor. Secs. 22 & 23

Alias 977030 Description Cor. #4 of HES 195
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Frederick W. Rase, Surveyor - Forest Service, Under special instructions dated March 23, 1916, Surveyed Aug. 1916 - (DCSO records C.S. File 65/67-7H)

Cor. No. 4 (70 ft. above river) identical with temporary stake set for 1/16 sec. cor. and cor. No. 4 of this survey, which I destroy and in its place.

Set a granite stone 30x12x6", 20" in the ground, over a stone mkd. with a cross for 1/16 sec. cor. and cor. No. 4 of this survey, mkd. 1/16 on west face and 4 HES 195 on side facing the claim - from which -

A fir 36" dia. bears N.82°15'E. 379 lks mkd X 4 HES 195 BT No other bearings available; therefore dig pits 24x24x12", crosswise on this and the succeeding line, 7 ft. dist. and raise a mound of earth 4 ft. base, 2 ft. high 3½ ft. dist. within the claim.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6723)

1/16 sec. cor. and cor. No. 4, HES No. 195, which is a granite stone, firmly set, 10x12x6" above ground, marked 1/16 on W. face, and 4 H E S 195 on E face; from which

A fir, 36" dia. bears N.82°15'E., 379 lks., marked
X 4 H E S 195 BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy & Crew - 2/5/1970 - C.S. File 54/59-133

Found - Old cor. stone firmly set & mkd: "X" on top & "4 HES 195" on claim side. The only orig. BT is gone. We find River calls to South & East, fit orig. call distances.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T30S R1W (Reset old stone alongside) OFFICE 1970 COR. #4 |HES 195
New BTs- 10" D.Fir S.62°W., 4.2 ft. mkd: 4 HES 195 CS BT.
9" D.Fir S.32°E., 17.8 ft. mkd: 4 HES 195 CS BT.

Note - This cor. is also the north 1/16 cor. of secs. 22 & 23, & lies on NE slope approx. 75 ft. East of top of spur sloping Southerly.