

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias 977020 Description Cor. #1 HES 195  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 73 dated June 8, 1857 - (DCSO Records Vol. 16 Page(s) 6672

-----  
Set post corner secs. 14, 15, 22, & 23, from which  
An Oak, 12" dia., bears N.75°W. 135 lks.  
An Oak, 8" dia., bears S.63°W. 85 lks.  
An Oak, 18" dia., bears N.10°E. 121 lks.  
An Oak, 15" dia., bears S.25°E. 168 lks.

GLO survey by Frederick W. Rase, Surveyor - Forest Service, Under special instructions dated March 23, 1916, Surveyed Aug. 1916 - (DCSO recs Vol. 16 Pg 6672, C.S. File 65/67-7D-F)

-----  
(7 D & E) Cor. Secs. 14, 15, 22, & 23 T30S R1W WM, which is a post (badly decayed) 3" sq. 12" above ground, marks not distinguishable; BTs as described by the Surveyor General remain standing.  
I destroy old post & in its place  
Set a granite stone 15x6x6" 10" in the ground, mkd. with 2 notches on east & 3 notches on south edges for cor. of secs. 14, 15, 22 & 23.  
(7 F) Begin at cor. No. 1 of this survey, identical with cor. of secs. 14, 15, 22, & 23 T30S R1W WM, heretofore described. I mark the stone with a cross on top for chaining point, and alongside of cor.  
Set a sand stone 26x10x8" 16" in the ground, over a stone mkd. with a cross, mkd. 1 HES 195 on side facing the claim, for cor. No. 1 of this survey.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6723-4)

-----  
The re-established cor. of secs. 14, 15, 22, & 23, and Cor. No. 1, HES No. 195, which is a granite stone, firmly set, 5x6x6" above ground, marked with 2 notches on E & 3 notches on S edge, with a sand stone alongside, firmly set, 10x10x8" above ground, marked 1 HES 195 on SE face; from which  
A pine, 26" dia., bears N.1°E., 125 lks., mkd: T30S R1E  
S14 BT: New BT. This tree also marked 1 HES 195.  
An Oak, 18" dia., bears S.27°E., 168 lks., mkd: T30S R1E  
S23 BT. old BT  
A pine, 26" dia., bears S.23°W., 149 lks., mkd: T30S R1W  
S22 BT. new BT.  
An oak, 12" dia., bears N.75°W., 135 lks., mkd: T30S R1W  
S15 BT: Old BT.

Cont.

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias 977020 Description Cor. #1 HES 195  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Douglas Co. Surveyors Office - John M. Powell - Frank Jones  
& W Penley - January 1968 - C.S. File 54/59-32

Found - Orig. stone at corner marked with notches.

\*\*1923 GLO brass cap at sec. cor. mkd:

General Land Office

T30S R1W

S 14 | S 15

S 22 | S 23

1923

26" now 29" Pine N.1°E., 82.5 ft. shows good scar.

12" now 16" Oak, N.75°W., 89.1 ft. opened for scribe

"T30"

New BTs- 11" D.Fir N.70°E., 41.1 ft. scribed T30S R1W S14 CS  
BT.

5" D.Fir N.73°W., 24.5 ft. mkd: S15 CS BT.

14" D.Fir S.75°W., 27.7 ft. mkd: T30S R1W S22 CS BT.

7" Pine S.72°E., 40.4 ft. mkd: T30S R1W S23 CS BT.

\*\* Did not find any record of a BC being set in 1923, DCSO-JC