

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 73 dated June 8, 1857 - (DCSO Records Vol. 16 Page(s) 6673

Set post corner secs. 10, 11, 14, & 15, from which
An oak, 24" dia., bears N.12°E. 155 lks.
An oak, 15" dia., bears S.82°E. 143 lks.
An oak, 12" dia., bears N.85°W. 219 lks.
A fir, 18" dia., bears S.87°W. 209 lks.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Feb. 1968 - C.S. File 54/59-74

Found - 24" now 36" B.Oak, N.12°E., 102.3 ft. shows good scars.
15" B.Oak, now dead, S.82°E., 94.4 ft. shows good scar.
12" now 18" W.Oak, N.85°W., 149.5 ft. (rec. 144.5) scribe marks visible but not legible. Tree rotten
No trace of 18" Fir SW
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T30S R1W
OFFICE S 10|S 11
1968 S 15|S 14
New BTs- 8" D.Fir N.35°W., 11.8 ft. mkd: T30S R1W S10 CS BT.
6" B.Oak S.55°E., 15.6 ft. mkd: T30S R1W S14 CS BT.
24" D.Fir S.56°W., 86.7 ft. mkd: T30S R1W S15 CS BT.

Loyd R. Moffit, LS #944 - For: USFS - May 1985 - C.S. 63/-148

Found - 2½" bronze cap on a iron pipe. (DCSO) 1968
A dead oak bears S.80°E., 95.2 ft. rotted blaze.
14" oak bears S.54°E., 15.0 ft. scar visible.
A fir stump bears S.58°W., 86.4 ft. scar visible.
A fir stump bears S.87°W., 133.4 ft. axe work visible.
26" oak bears N.83°W., 147.5 ft. scar visible
14" fir bears N.33°W., 12.0 ft. scribe visible.
50" oak bears N.14°E., 101.8 ft. scar visible.
New BT - 10" oak bears S.47°W. 9.4 ft scribed T30S R1W S15 BT