

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 73 dated June 8, 1857 - (DCSO Records Vol. 16 Page(s) 6674</p> <p>-----</p> <p>Set ¼ sec. post, from which A dogwood, 12" dia., bears S.55°W. 20 lks. A fir, 12" dia., bears N.22°E. 22 lks.</p>
<p>GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 16 Pgs 6698-9)</p> <p>-----</p> <p>¼ Sec. corner which is a fir post 4" sq. 16" above ground, marked & witnessed as described by the surveyor general.</p>
<p>Not fd per DCSO JMP, 2/1968 - C.S. File 54/59-75 Not fd per USFS Tiller Ranger Dist. 11/1973 - C.S. 56/40-44.</p>
<p>Bruce Shaner, PLS #430 - For: Tiller Ranger Dist. Umpqua Nat'l Forest - Nov. 1980 - M79-63</p> <p>-----</p> <p>Set - Brass cap mkd: T30S R1W WM ¼ S, S10, S11, RLS 430, 1980 BTs - 18" D.Fir BT, scribed "¼ S10 BT" bears S.30°W., 44.8 ft 10" D.Fir BT, scribed "¼ S11 BT" bears S.59°E., 47.7 ft</p>
<p>FD. Ok By B. Shaner, 7/1999 - M132-9 - C.S. File 65/23-15</p>