

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor. Secs 2, 3, 10, & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, US Deputy Surveyor under contract 73 dated June 8, 1857 - (DCSO Records Vol 16 Pg 6674

Set post corner secs. 2, 3, 10, & 11, from which
A maple, 12" dia., bears S.8°W. 39 lks.
A maple, 10" dia., bears S.68°E. 22 lks.
A fir, 48" dia., bears N.85°E. 52 lks.
A chinquapin, 8" dia., bears N.10°W. 37 lks.

GL0 corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 16 Pg 6691E)

Cor. of secs. 2, 3, 10, & 11 which is nearly obliterated. The old cor. which was a post has disappeared. The fir & maple described as BTs in secs. 2 & 10 are standing, with marks deep overgrown & nearly indistinguishable. No trace found of the other BTs.
Obliterate the old marks & reestablish the corner in its orig. position as follows:
Set a basalt stone 18x16x8" 12" in the ground for cor. of secs. 2, 3, 10, & 11, marked with 5 notches on S & 2 notches on E edge, from which
A W.Fir, 12" dia., bears N.58°E., 76 lks., mkd: T30S R1W S2 BT.
A W.Fir, 20" dia., bears S.78°E., 123 lks., mkd: T30S R1W S11 BT.
A maple, 16" dia., bears S.37°W., 30 lks., mkd: T30S R1W S10 BT.
A R.Fir, 60" dia., bears N.38°W., 68 lks., mkd: T30S R1W S3 BT.

Thomas Shrum - For: US Plywood-Champion Papers Inc. - June 1967 (FILED 7/18/1968) - M36-14

Found - Maple 24" S.26°W.
Maple 18" S.08°W., 25.70'
Fir 60" N.35°W., 40.00'
Fir 50" N.85°E., 34.30'
Hemlock, S.75°E.
Set - Fir 9" S.57°W., 14.70'
Fir 9" N.71°W., 28.50'
2½" Alum. cap.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage & V. Perron - Nov. 1, 1967 - C.S. File 54/59-1

Found - 1967 U.S. Plywood Alum. cap, properly marked but unrecorded. (Filed 7/18/1968) continued

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor Secs 2, 3, 10, & 11

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Orig. 12" now 18" maple, alive, S.8°W., 25.7 ft. rotted out, no scribe.
Orig. 48" now 60" fir, N.85°E., 34.3 ft. no scar or bark scribe.
No trace Hathorn's BTs, SE or NW
We find other orig. BTs, unrecorded.
40" W.Fir S.75½°E., 83.8 ft. alive, previously opened & shows scribe.
72" D.Fir, alive, N.36°W., 39.7 ft. shows good scar.
Shrums new BTs as follows: (M36-14)
9" W.Fir S.63°W., 14.5 ft. mkd: "S10 BT"
9" W.Fir N.66°W., 28.5 ft. mkd: "S 3 BT"
Note - We do not find a branch 1 lk. wide 6.6 ft. S of corner as called for.

Fd. Ok DCSO JMP 2/1968 - C.S. File 54/59-72

Russell Badgley - 7/2021 - C.S. File 65/109-28

Condition report only
Found - A 2" aluminum post firmly set, projecting 3" above the ground with a 2½" dia alum cap (properly) mkd
Orig. BTs -
A 23" dia. Maple bears (Rec. S.8°W. 25.7') with no scribe.
A 65" dia. D.Fir bears (Rec N.85°E. 34.3') with bark blaze.
Other Orig. BTs recorded by DCSO -
A 68" dia. D.Fir bears (Rec. N.36°W. 39.7') with healed blaze.
BTs by Shrum per M36-14 -
A 12" dia. W.Fir high stump bears (Rec. S.63°W. 14.5') with partially healed blaze.
A 14" W. Fir bears (Rec. N.66°W. 28.5') feet with a healed blaze.
Note - Compass declination: 14°30'E.