

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO corrective survey by Fred Mensch, Dep. Surveyor, Contract #757 dated Sept. 14, 1904 - (DCSO records Vol. 16 Page 6688)

-----  
Set a basalt stone 14x12x6", 9½" in the ground for ¼ sec. corner marked ¼ on W face; from which

A R.Fir, 30" dia., bears N.25°E., 49 lks., mkd: ¼ S2 BT.

A Cedar, 15" dia., bears S.70°W., 66 lks., mkd: ¼ S3 BT.

-----  
Dennis Gaylord, USFS & Deputy Co. Surveyor - Witness: Randal Lopez - Nov. 17, 1977 - C.S. File 59/42-16

-----  
Found - Stone 12x10x6" set solidly in the ground, marked "¼" on the NW face.

A 23" Cedar stump bears S.70°W., 43.2 ft. (Rec. 43.56 ft.) Traces of scribing visible on burned face.

A 45" D.Fir bears N.25°E., 29.6 ft. (Rec. 32.34 ft. slope dist. is 32.5 ft. at 45%) has a healed blaze.

Set - Moving the stone aside, I set in its place a 2½" brass cap on a 1" IP marked:

COUNTY SURVEYORS OFFICE T30S R1W  
1977 ¼ S3 S2

I buried the corner stone alongside.

New BT - A 13" Yew bears N.81°W., 11.2 ft. scribed "¼ S3 CS BT" on a double blaze.

Placed county BT signs on all three accessories.