

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 520360

PRIMARY CORNER DESCRIPTION NW 1/16 Cor. Sec. 23

Alias 977040 Description HES 195 Cor # 3
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Frederick W. Rase, Surveyor - Forest Service, Under special instructions dated March 23, 1916, Surveyed Aug. 1916 - (DCSO records C.S. File 65/67-7G)

Cor. No. 3 (point intended by the District Forester) 450 ft. below cor. No. 2.

Set a granite stone 24x10x5", 14" in the ground, over a stone mkd. with a cross for cor. No. 3 of this survey, mkd. 3 HES 195 on side facing the claim - from which -

A fir 6" dia. bears N.74°30'W., 23 lks., mkd. X 3 HES 195 BT.

No other bearings available; pits impracticable.

Raise a mound of stone 3 ft. base, 2 ft. high, 3½ ft. dist. within the claim.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6741)

Cor. No. 3 which is granite stone firmly set, 10x10x5" above ground, marked 3 H E S 195 on NW face; from which

A yew, 6" dia., bears S.73½°W., 23 lks., mkd: X 3 H E S 195 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy & Crew - 2/5/1970 - C.S. File 54/59-131

Found - Old cor. stone in place & mkd: "3 HES 195 on claim side.

Orig. 6" yew, now 10" S.73½°W., 15.2 ft. alive, scribe visible on decaying blaze.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS T30S R1W

(Reset old stone alongside) OFFICE 1970 COR. #3 HES 195

New BTs- 9" D.Fir N.19°W., 18 ft. mkd: 3 HES 195 CS BT.

18" D.Fir S.86°E., 17.1 ft. mkd: 3 HES 195 CS BT.

Note - This cor. lies on very steep Southerly slope, between road & Jackson Creek.