

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 520400

PRIMARY CORNER DESCRIPTION W 1/16 Cor. Secs. 14 & 23

Alias 977010 Description Cor. #2 HES 195
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Frederick W. Rase, Surveyor - Forest Service, Under special instructions dated March 23, 1916, Surveyed Aug. 1916 - (DCSO records C.S. File 65/67-7F)

Cor. No. 2 and 1/16 sec. cor., identical with the temporary stake already set, which I destroy and in its place Set a granite stone 24x7x6", 14" in the ground over a stone mkd. with a cross for 1/16 sec. cor. and cor. No. 2 of this survey, mkd. 1/16 on north face and 2 HES 195 on side facing the claim: - from which -
A fir 12" dia., bears S.10°30'W., 88 lks., mkd: X 2 HES 195 BT.
A fir 14" dia., bears S.25°00'W., 97 lks., mkd: X 2 HES 195 BT.
Raised a mound of stone 3 ft. base, 2 ft. high, 3½ ft. dist. within the claim.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6724-5)

1/16 Sec. cor. and cor. No. 2, HES No. 195, which is a granite stone, firmly set, 10x7x6" above ground, mkd. 1/16 on N & 2 HES 195 on S face from which
A fir 12" dia., bears S.10°30'W., 88 lks. mkd: X 2 HES 195 BT.
A fir 14" dia., bears S.25°W., 97 lks., mkd: X 2 HES 195 BT.
With mound of stone SW of cor.

Reported as not found by DCSO, VRT 2/1970 - Fd. E-W blazed & N-S blazes - area as described in Forrest appr. no cor. stone or OBTs Fd. C.S. File 54/59-132

Douglas Co. Surveyors Office - Dennis Gaylor, USFS & Deputy Co. Surveyor - witness: Walt Barton - April 7, 1977 - C.S. File 59/31-21

Found - No monument fd. Corner location falls in center of a skid trail. Orig. corner monument destroyed.
A broken & decayed 13" Fir stob bears S.10°30'W., 58.08 ft. Scribing visible "X2 HES 195 BT"
A 30" fir stump bears S.35°W., (rec. S.25°W.) 64.02 ft. Open & find scribing "95 BT"

cont. next page

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 520400

PRIMARY CORNER DESCRIPTION W 1/16 Cor. Secs. 14 & 23

Alias 977010 Description Cor. #2 HES 195
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set - At the intersection of record distances from the two orig. BTs: A 2½" brass cap flush with the ground
mkd: County Surveyors Office T30S R1W Cor. | HES 1977
No. 2 | 195

Placed a 2'x2' mound of stone around the downhill (south) side of the pipe.

New BTs- A 26" D.Fir bears S.26°E., 22.2 ft. scribed "X2 HES 195 CS BT" on a double blaze.

A 16" D.Fir bears S.11°W., 20.9 ft. scribed "X2 HES 195 CS BT on a double blaze.

Placed county BT tags on both trees.

Note - Corner lies 75 ft. north of old road used for former logging access. (16°E dec. rock in area)