

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for sec. 35 only

| Alias | Description |
|-------|-------------|
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6649)

Set $\frac{1}{4}$ sec. post, from which
A Fir 15" dia., bears N.88°E., 73 lks.
A Fir 12" dia., bears S.88°E., 80 lks.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6712)

The old $\frac{1}{4}$ sec.cor., located by reference to the original bearing trees. From cor. point,
A Fir 30" dia., bears N.88°E., 73 lks. dist. mkd. $\frac{1}{4}$ S BT.
(Old BT)
A Fir 12" dia., bears S.88°E., 80 lks. dist. mkd. $\frac{1}{4}$ S BT.
(Old BT)

I now change this cor. to refer to sec. 35 only, and obliterate the marks on the bearing tree SE. of cor.
At exact cor. point
Set an Iron post 3 ft. long, 1" dia., 28" in the ground for $\frac{1}{4}$ sec. cor. of sec. 35 only, with brass cap mkd: $\frac{1}{4}$ S 35
1923

from which
An Oak 8" dia., bears N.18°W., 66 lks. dist. mkd. $\frac{1}{4}$ S35
BT. (New BT)