

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

1922 16" red fir, now 21" scribed "¼ S35 CS BT" in a single blaze bears S.60°E., 20.5 ft. meas. from 1922 face. Portion of orig. scribing "5B" still visible, tree is from 1922 Mensch resurvey.

Possible orig. 48" fir, present size indeterminable, now a 3 ft. tall stump bears S.82°W., 6.1 ft. (Rec. S.88°W., 5.9 ft.) Record distance probably taken to bark. We find the record bearing 6° too far right. Mensch, in 1922, found an orig. 8" fir N.60°E., 13.2 ft. from the corner (rec. N.70°E., 19.8 ft.) i.e. record bearing 10° too far right. No sign of blaze or scribing.

24" cedar, now a fallen 20" stob 8 ft. tall scribed "¼ S26 CS BT" in double blaze. Root hole bears N.46°E., 20.6 ft.

Original 8" fir not found. (Rec. N.60°E., 13.2 ft.)

Corner position was established using record position from 1922 16" red fir (N.60°W., 20.5 ft.). We reset 1968 monument and set corner stone on the north side of the monument. We add the words "Reset 1984" to brass cap.

Accessories:

- Set boat spike stamped "BO 1" thru BT tag In orig. 48" stump (not in center) bears S.82°W., 7.2 ft.
- 9" D.Fir bears N.8°W., 78.5 ft. and is scribed "¼ S26 CS BT" in double blaze.
- 8" yew bears S.80°E., 33.5 ft. and is bark scribed "¼ S35 CS BT"
- 10" yew bears S.9°W., 41.4 ft. and is scribed "¼ S35 CSBT" in double blaze.