

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6738)

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor. with brass cap marked

1/4 S23
 S26
 1923

from which
A cedar, 10" dia., bears S.1°W., 23 lks., mkd: 1/4 S26 BT.
A fir, 12" dia., bears N.34°W., 17 lks., mkd: 1/4 S23 BT.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung - 11/23/2019 (Filed 11/17/2021) - C.S. File 67/50-11

Found A 1" i.d. iron pipe, firmly set, projecting 8" above the ground in a 12" dia. x 5" high mound of stone with a 3 1/4" dia. brass cap (properly) marked
No Evidence of original trees. Root holes possibly washed away by seasonal stream.

New - A 17" dia. D.Fir bears N.88°E., 13.7 ft scribed "1/4S23CS" "BT".
 A 13" dia. P.Pine bears S.2°W., 19.7 ft scribed "1/4S26CS" "BT".
 A 26" dia. I.Cedar bears S.77 1/2°W., 31.0 ft scribed "1/4S26" "CSBT".
 A 13" dia. D.Fir bears N.37°W., 7.6 ft scribed "1/4S23" "CSBT".

Note - The corner falls on flat bench land Northeasterly of gravel access road approximately 150 ft. in a mixed fir and pine forest, S.45°W., 10.0 of a North running seasonal stream.
All BTs have BT Tags attached. All new BTs have double blazed faces with bearing measured to the center of the tress at the root crown and distances measured to a 4" mag nail in the side and center of the root crown.
Compass declination 14 3/4°E.

Geodetic coordinates
LAT: 42°56'44.540263291" N. LONG: 122°47'34.800852750" W.
DATUM NAD 83 SOURCE: GeoXT6000