

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 73 dated June 8, 1857 - (DCSO Records Vol. 16 Page(s) 6676

-----  
Set ¼ sec. post, from which  
A pine, 15" dia., bears N.80°E. 19 lks.  
A fir, 18" dia., bears S.35°E. 70 lks.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6725)

-----  
Point for the ¼ sec. cor. which I locate by reference to orig. BTs.  
Set an iron post 3 ft. long, 1" dia., 28" in the ground for ¼ sec. cor., with brass cap mkd.  $\frac{1}{4} \begin{array}{l} S 14 \\ S 23 \\ 1923 \end{array}$

from which  
A pine, 15" dia., bears N.80°E., 19 lks., mkd: ¼ S14 BT:  
old BT.  
A fir, 18" dia., bears S.35°E., 70 lks., mkd: ¼ S23 BT:  
Old BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Feb. 1968 - C.S. File 54/59-69

-----  
Found - GLO brass cap, 1923, properly marked.  
15" now 24" Pine, N.80°E., 12.5 ft. shows scribing.  
No trace of SE BT.  
New BT - 24" D.Fir S.34°E., 32.4 ft. mkd. ¼ S23 CS BT.  
Note - This corner lies approx. 40 ft. north of a E-W cutting line.