

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 2 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 14 Page(s) 6060)

Set ¼ sec. post, from which
A Fir 12" dia., bears N.75°E., 9 lks. dist.
A Fir 12" dia., bears S.70°W., 10 lks. dist.

GLO Resurvey by Ernest P. Rands, Deputy Surveyor, Under contract #790, dated Oct. 18, 1909 - (DCSO records Vol. 14 Page(s) 6104)

Intersect the old ¼ sec. cor.
The post and 1 bearing tree have been destroyed. By reference of the remaining bearing tree, I locate the original cor. where I SET a granite stone, 15x8x7 ins., 10" in the ground for ¼ sec. cor. common to 2 quarters only, mkd. ¼ on S. face, from which
The original Fir, 12" dia., bears N.75°E., 9 lks. dist.
A Fir 18" dia., bears S.19¼°E., 64 lks. dist. mkd. ¼ S35 BT. (New BT)
From this corner, Frank L. George's barn bears North 1.45 chs. dist.

Thomas Shrum - for: U.S. Plywood - Champion Papers Inc. - June 1967 - M 36-14

Found - Fir, 18", S.20°E., 42.20 ft.
Stone
Set - 2½" Aluminum cap.

Douglas Co. Surveyors Office - John M. Powell, and crew - Feb. 7, 1968 - C.S. File 54/59-64

Found - Unrecorded 1967 alum. cap mkd. USPC Prop. Cor. T29S R1W RE 4297 1967 (See Shrum survey, M 36-14)
No trace of NE. BT.
18" D.Fir now stump, S.19°E., 42.2 ft., open for scribe.
Stone, firmly set at ¼ cor. mkd. ¼ on S. face.
New BTs- 7" R.Fir S.47°W., 14.7 ft. mkd. ¼ S2 CS BT.
9" D.Fir S.11½°W., 21.3 ft. mkd. ¼ S2 CS BT.
Cor. lies approx. 50 ft. N. of logging road.

(Cont. next page)

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 540700

PRIMARY CORNER DESCRIPTION No. 1/4 cor. Sec. 2 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Ronald Geisler, LS #1988 - For: Champion International -
July 18, 1986 - C.S. File 63/34-37

Found - 2½" alum. cap on a 1" I.P., extends 14" above
ground.

(1967) 9" W.Fir bears S.47°W., 14.6 ft. closed face.

19" Fir, stump, bears S.20°E., 42.2 ft. closed
face. (1967)

New BT - 6" W.Fir bears S.30°E., 18.06 ft. and scribed "¼
S2 BT".