

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 35 only, East

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 73 dated June 8, 1857 - (DCSO Records Vol. 16 Page(s) 6675)

-----

A fir 18" dia., ¼ sec. corner, from which  
A fir, 12" dia., bears S.30°E., 40 lks.  
A fir, 9" dia., bears N.45°W., 6 lks.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6716-7)

-----

The point for the ¼ sec cor established for secs 35 & 36, which I locate by reference to the orig BTs. I now change this cor. to refer to sec. 35, only, & at the exact cor point Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor. of sec. 35 only, with brass cap marked

¼S35  
1923 | from which

A dead fir, 12" dia., bears S.30°E., 40 lks., mkd: ¼ S BT:  
Old BT. I destroy these marks.  
A dead fir, 9" dia., bears N.45°W., 6 lks., mkd: ¼ S BT:  
Old BT  
A fir, 30" dia., bears S.16°W., 49 lks., mkd: ¼ S35 BT:  
New BT.  
A fir, 36" dia., bears N.78°W., 52 lks., mkd: ¼ S35 BT:  
New BT.