

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26 & 35; only (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 73 dated June 8, 1857 - (DCSO Records Vol. 16 Page(s) 6675

Set post center corner secs. 25, 26, 35, & 36, from which
A fir, 18" dia., bears N.52°E., 14 lks.
A fir, 20" dia., bears S.48°E., 60 lks.
A fir, 18" dia., bears S.15°W., 50 lks.
A cedar, 15" dia., bears N.36°W., 65 lks.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6717-8)

The cor. established for secs. 25, 26, 35, & 36, located by reference to the orig. BTs. The NE BT is dead, but standing, with marks still legible. The SE & SW trees are burned stubs and the NW tree is burned out, but all are identified & are in the position in the field notes.

At the exact corner point
Set an iron post 3 ft. long, 2" dia., 26" in the ground for cor. secs. 26 & 35 only, marked

T30S		
S 26		
S 35		S 25
R1W		

1923 from which
A fir, 10" dia., bears S.45°W., 23 lks., mkd: T30S R1W
S35 BT. New BT
A fir, 12" dia., bears N.8°W., 40 lks., mkd: T30S R1W
S26 BT. New BT

Fd. ok by JMP, DCSO - 1/26/1968 - C.S. File 54/59-56