

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 600239

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 25 only, west

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6735)

-----  
(40 chs. northing from cor. of secs. 25 & 36) Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor. of sec. 25 only, with brass cap marked 1/4 S25  
1923

from which  
A fir, 20" dia., bears N.59°E., 51 lks., mkd: 1/4 S25 BT.  
A fir, 14" dia., bears S.78°E., 47 lks., mkd: 1/4 S25 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Jan-Feb 1968 - C.S. File 54/59-54

-----  
Found - 1923 GLO Brass Cap at Cor. Mkd. properly.  
14" R.Fir, now stob, S.78°E. 31.0 ft., scribe visible "1/4 S25 BT".  
No trace of N.E. Bearing Tree.  
New BTs- 36" Fir N.31 1/2°E. 40.8 ft. mkd. 1/4 S25 CS BT.  
12" Fir S.7°E. 11.9 ft. mkd. 1/4 S25 CS BT.  
Note - This corner lies 61.4 ft. south of section 26 only which is O.K.