

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 600240

PRIMARY CORNER DESCRIPTION 1/4 Sec. 26 only, East

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6735)

Midpoint on E bdy. of sec. 26
Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for 1/4 sec. cor. of sec. 26 only, with brass cap marked

1/4 S26 |
1923

from which

- A fir, 42" dia., bears S.78°W., 25 lks., mkd: 1/4 S26 BT.
- A cedar, 16" dia., bears N.11°W., 31 lks., mkd: 1/4 S26 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones - W. Penley - Jan./Feb. 1968 - C.S. File 54/59-55

Found - 1923 GLO brass cap, properly marked at 1/4 corner.
42" D.Fir, now 42" S.78°W., 16.5 ft shows good scar.
16" now 17" Cedar N.11°W., 20.5 ft. scribed visible,
tree being smothered, not in good condition.

New BT - 15" Fir N.10°W., 37.7 ft. mkd: 1/4 S26 CS BT.

Note - This corner lies 61.4 ft. north of 1/4 S25 only.