

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 73 dated June 8, 1857 - (DCSO Records Vol. 16 Page(s) 6676

Set post corner secs. 13, 14, 23, & 24, from which
A fir, 12" dia., bears S.85°W., 50 lks.
A fir, 6" dia., bears N.35°W., 48 lks.
A fir, 6" dia., bears N.14°E., 33 lks.
A fir, 4" dia., bears S.20°E., 21 lks.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6725-6)

The cor of secs 13, 14, 23 & 24 which is identified by a small mound of stone & fragments of the old post. The NW & SW BTs are dead & the NE tree is not fd. The SE tree is an oak instead of a fir as reported. In the position of the old post Set an iron post, 3 ft. long, 1" dia., 12" in the ground to bedrock, supported by mound of stone for cor. of secs. 13, 14, 23, & 24, with brass cap marked

T30S R1W
S 14 | S 13
S 23 | S 24

1923 from which
An Oak, 6" dia., bears N.9°E., 25 lks., mkd: T30S R1W S13
BT. new BT
An Oak, 5" dia., bears S.20°E., 21 lks., mkd: T30S R1W S24
BT. Old BT
A fir, 14" dia., bears S.65°W., 56 lks., mkd: T30S R1W S23
BT. New BT
A fir, 12" dia., bears N.71°W., 45 lks., mkd: T30S R1W S14
BT. New BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Dec. 20, 1967 - C.S. File 54/59-7

Found - GLO Brass Cap, properly marked in 1923.
5", now 8" Oak, S.20°E. 13.9 ft., shows scar.
14" D.Fir, now dead, S.65°W. 36.7 ft. opened for scribe "BT".
12" D.Fir, now dead, N.71°W. 32.0 ft. (record 29.7 ft.) opened for scribe
No trace of N.E. Bearing Tree.
New BTs- 7" W.Oak N.15°W. 16.0 ft. mkd. T30S R1W S14 CS BT.
6" W.Oak N.10°E. 16.3 ft., mkd. T30S R1W S13 CS BT.
18" D.Fir S.9°W. 42.0 ft., mkd. T30S R1W S23 CS BT.

