

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 73 dated June 8, 1857 - (DCSO Records Vol. 16 Page(s) 6676

Set ¼ sec. post, from which
A pine, 10" dia., bears N.50°E., 22 lks.
An Oak, 8" dia., bears N.64°W., 21 lks.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6726-7)

The ¼ sec. cor., located by reference to the orig. BTs, both dead, but in the position described in the field notes.

At the exact corner point
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap marked
S14|S13
1923

from which
A B.Oak, 7" dia., bears S.6°E., 261 lks., mkd: ¼ S13 BT.
New BT.
A pine, 13" dia., bears N.44¾°W., 253 lks., mkd: ¼ S14 BT.
New BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - July 1968 - C.S. File 54/59-121

Found - U.S. G.L.O. Brass Cap, properly marked in 1923, from which:
13" Pine, now 15" Stump, N.44¾°W. 167.0 ft., opened & found scribing of "4"
No trace of SE. Bearing Tree.
New BTs- 8" Sugar Pine S.41°E., 9.1 ft. mkd. "¼ S13 CS BT".
7" D.Fir N.45°W., 16.3 ft. mkd. "¼ S14 CS BT".