

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6734)

Set an iron post, 3' long, 1" dia., 27" in the ground, with brass cap marked:

¼ $\frac{S\ 25}{S\ 36}$
1923

from which

A fir, 12" dia., bears N.16½°E., 148 lks., mkd: ¼ S25 BT.

A fir, 8" dia., bears S.7½°W., 123 lks., mkd: ¼ S36 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - Jan. 1968 - C.S. File 54/59-44

Found - 1923 GLO Brass Cap at ¼ Cor., properly marked. 12", now 22" D.Fir, N.16½°E. 97.7 ft., shows good scar.

8", now 19" D.Fir S.7½°W. 81.2 ft., opened for scribe "S"

New BTs- 9" D.Fir N.17½°W. 5.7 ft. mkd. ¼ S25 CS BT.

9" D.Fir S.22°E. 17.6 ft. mkd. ¼ S36 CS BT.