

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 12 & 13

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, US Deputy Surveyor under contract 73 dated June 8, 1857 - (DCSO Records Vol. 16 Page(s) 6677

-----  
Set ¼ sec. post, from which  
A fir, 6" dia., bears N.50°W., 50 lks.  
A pine, 15" dia., bears S.28°E. 156 lks.

GLO survey by Fred Mensch, US Cadastral Engineer - Under special instructions dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6728)

-----  
The ¼ sec. cor. located by reference to the orig. SE BT, no other evidence found.  
At the exact corner point  
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for ¼ sec. cor., with brass cap marked S 12 ¼  
S 13  
1923

from which  
A pine, 36" dia., bears S.28°E., 156 lks., mkd: ¼ S13 BT.  
Old BT.  
A pine, 24" dia., bears N.20°W., 133 lks., mkd: ¼ S12 BT.  
New BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - 7/1968 - C.S. File 54/59-123

-----  
Found - US GLO brass cap, properly marked in 1923  
36" now 39" Pine, S.28°E., 103.0 ft shows good scar.  
24" now 30" Pine, N.20°W., 87.8 ft. shows good scar.  
New BTs- 15" D.Fir S.41°W., 11.2 ft. mkd: ¼ S13 CS BT.  
8" D.Fir N.15°E., 10.2 ft. mkd: ¼ S12 CS BT.  
Note - This corner lies approx. 50' S of E-W fence post line & west of N-S fence line, approx. 75.0 ft.

William Ruppert, LS #866 - For: US Forest Service - Jan. 1978 - M65-80

-----  
Found - 1923 US GLO brass cap properly marked.  
32" P.Pine, N.19°24'W., 87.4 ft. good scar.  
10" D.Fir, N.10°10'E., 10.0 ft. vis. scar.  
37" P.Pine S.27°21'E., 103.5 ft. good scar.  
15" D.Fir fallen, S.37°25'W., 10.8 ft. good scar.  
Scribed- 13" D.Fir S.65°19'W., 58.6 ft. scribed "¼ S13 BT"

continued next page

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 12 & 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Loyd R Moffit LS #944 - For: USFS - May 1985 - C.S. File 63/8-16

-----

Found - A 1923 GLO brass cap on a 3/4" iron pipe.  
A 12" dead fir bears N.15°E., 10.1 ft scribe visible  
A 16" fir, down, bears S.41°W., 11.4 ft healed blaze  
A 14" fir bears S.72°W., 58.6 ft. scribe visible.  
(Rec. S.65°19'W.)\*\* **Geisler fd to be S.65°W.**  
A pine stump (orig. BT) bears N.17°W., 87.4 ft. scar visible.  
A 40" pine (orig. BT) bears S.25°E., 103.5 ft. scribe visible.  
New BT - 10" Fir which bears East 9.4 ft. scribed ¼ S12 BT.

\*\*Fd. Ok 4/1986 by R. Geisler, C.S. File 63/34-7