

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 16 Page(s) 6654)

Set post corner secs. 18, 19, 13 and 24, from which
A Fir 12" dia., bears S.1°W., 35 lks.
A Fir 12" dia., bears N.30°W., 59 lks.
A Maple 12" dia., bears N.47°E., 40 lks.
A Hemlock 10" dia., bears S.30°E., 50 lks.

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract #746, dated May 5, 1902 - (DCSO records Vol. 16 Page(s) 6683)

(From cor. for 13 & 24 only, this cor. bears N.83°07'W., 29.60 chs.) The stake is completely decayed but is witnessed as described by the surveyor general. In the place of the stake at the original point, I set
A basalt stone 20x14x10 ins., 15" in the ground for corner of secs. 13 and 24, marked with 3 notches on N. and S. edges. I destroy all marks on the corner referring to T30S R1E.

GLO resurvey by Fred Mensch, U.S. Deputy Surveyor - under Special Instructions, dated June 7, 1922 - (DCSO records Vol. 16 Page(s) 6732)

(On "old" E. bdy. of sec. 13)
Fall 121 lks. W. of the cor. established by Hathorn as the cor. of secs. 13, 18, 19 and 24, located by measurement from the original bearing trees which are in agreement with the field notes, except that the NE. tree bears N.31°E., instead of N.47°E., as reported. The SE. and NW. trees are dead.
At exact cor point
Set an iron post 3 ft. long, 2' dia., 27" in the ground for SE. cor. of original sec. 13, with brass cap marked:

T30S
R1W
S13

S24

from which
A Fir 16" dia., bears S.1°W., 35 lks. dist. mkd. T30S R1W S24 AP BT. (Old BT)
A Fir 38" dia., bears N.6°W., 62 lks. dist. mkd. T30S R1W S13 BT. (New BT)
I obliterate marks on former tree intended in the original survey to refer to sec. 18, T30S R1E.

(Cont. Next Page)

TOWNSHIP 30 RANGE 01 POINT IDENTIFIER # 668400

PRIMARY CORNER DESCRIPTION NW, Cor, Govt, Lot #2, Sec. 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - John M. Powell, and crew -
Sept. 23, 1971 - C.S. File 54/59-138

Found - 1923 GLO brass cap at cor. as mkd. in 1923.
16" D.Fir now burnt stob, S.1°W., 23.1 ft. Scribe
visible "T30S R1W S24"
38" D.Fir now stump, N.6°W., 40.9 ft.
New BTs- 8" Hemlock N.8°E., 25.6 ft. scribed T30S R1W S13 CS
BT.
36" D.Fir S.77°W., 15.4 ft. scribed T30S R1W S24 CS
BT.
Corner lies on East slope approx. 90.0 ft. West of draw.